

GZP6189A Series

Vacuum Brake Pressure Sensor

Analog Output

Datasheet

Version: V1.3

Issued Date:2024.05.28

Table of contents

1. Product Description	4
1.1 Features	4
1.2 Application Areas	4
2. Function Description	5
2.1 Electrical Connections	5
2.2 Block Diagram	6
2.3 Pressure Function	6
2.4 Accuracy	6
2.4.1 Overall Accuracy	7
3. Technical Specifications	8
4. Structure and Specification	8
5. Order Guide	9
6. Installation Instructions	9
7. Precautions for use	10

Document Revision History

Revision	Description	Date
V1.0	Initial version	2022.05.13
V1.1	Modify the recommended size of the mounting holes	2022.09.01
V1.2	Template modification	2023.02.07
V1.3	Increase product series	2024.05.28

The company reserves the right to change the specifications included therein without prior notice. The copyright of the product specifications and the right to final interpretation of the product belong to Sencoch.

1. Product Description

GZP6189A vacuum-Brake pressure sensor is a finished pressure sensor launched by Sencoch for the automobile market.

Using the MEMS piezoresistive effect, when the sensor is affected by the pressure change in the vacuum-Brake system, its internal resistance value will change accordingly. By measuring the change in the resistance value, the size of the pressure is reflected, and the pressure signal is converted into electrical signal output, so that the vehicle's electronic control system can monitor and the sensor has the advantages of fast response, high accuracy, good stability and low cost. It is a cost-effective pressure sensor product.

1.1 Features

- Pressure range: 10~115kPa
- High accuracy, fast response
- Working temperature range -40°C to 130°C
- Overvoltage and reverse polarity protection
- Proportional analog voltage output with clamp set (customizable)
- Extensive automotive applications with affordable cost



1.2 Application Areas

The product is installed on the braking vacuum pipeline system, which is used to monitor the vacuum degree in the current braking vacuum pipeline and feedback the size of the current braking assistance. The pressure sensor converts the detected pressure into an electrical signal and inputs it into the vehicle's control system.

2. Function Description

This product is manufactured using advanced microelectromechanical principles. Its core technologies are a silicon piezoresistive effect- based MEMS pressure sensor chip and a high-performance signal conditioning ASIC chip. The silicon micro-piezoresistive MEMS pressure sensor chip outputs a voltage signal proportional to the measured pressure through a Wheatstone bridge composed of four strain-sensitive resistors. This signal is amplified, temperature-compensated, and linearized by the ASIC chip to obtain an output voltage that is proportional to the applied pressure. Linearization of the transfer function and temperature compensation are implemented by digital processing circuitry in the ASIC. Through polynomial compensation algorithms and multi-point pressure calibration technology at multiple temperatures, high-precision pressure measurement is achieved across the entire operating temperature range. The transfer function of the pressure sensor is created by the following parameters:

- Minimum and maximum rated pressure
- Voltage values at minimum and maximum rated pressure
- Clamping voltage

All parameters required for the complete calibration algorithm (such as offset, gain, temperature coefficients of offset and gain, and linearization parameters) are determined and stored in the E²PROM inside the ASIC after calibration.

2.1 Electrical Connections

The recommended female electrical connector for this product is AMP C-282688.




Fig.1 Pin diagram

The above connector is for Delphi interface. For other connector types and sizes, please consult Sencoch.

Tab.1 Pin Correspondence

Serial Number	Describe	Remark
1	VCC	Power input positive terminal 5±0.25VDC
2	Vout	Product output voltage signal
3	GND	negative power input

2.2 Block Diagram

The sensor functional block diagram is shown in Figure 2.




Fig.2 Sensor Functional Block Diagram

2.3 Pressure Function

P indicate the input pressure (the difference between inlet pressure and atmospheric pressure), in kPa. Vout is the output voltage, in volts (V).

The curve formula: $V_{out} = (0.008095 * P - 0.000952) * V_{cc}$ and linear equation is shown in Figure 3:




Fig.3 Voltage output curve

2.4 Accuracy

The accuracy of the GZP6189A pressure sensor is affected by the supply voltage, input pressure, ambient temperature, and aging effects. The value calculated using the transfer function is the sensor's specified value, which is also its theoretical value. The sensor's error is equal to the difference between the actual output voltage value and the specified output voltage value at the specified input pressure.

2.4.1 Overall Accuracy

The overall accuracy takes into account different error sources within the measurement pressure range and operating temperature range. These error sources mainly include:

Pressure: The output deviation between the actual output voltage and the specified output voltage within the specified pressure range.

Temperature: Output deviation at different temperatures within the temperature range.

Aging: The drift of parameters over time.

The overall accuracy is represented by an error band, which consists of three-line segments. The data is shown in Figure 4 as shown.




Fig.4 Relationship between overall accuracy and temperature

3. Technical Specifications

The following sensor specifications were measured at a power supply of (5±0.25) V DC and a temperature of 25°C.

3.1 Maximum Rated Parameters

The maximum rated parameters of the sensor are shown in Table 3.

Tab.3 The maximum rated parameters

Attribute	Minimum	Typical	Maximum	Unit	Remark
Maximum voltage			18	V	1h
Reverse voltage			-14	V	
Overload pressure			500	k PaG	60s
ESD protection			±4	KV	

3.2 Performance Indicators

The sensor performance indicators are shown in Table 4.

Tab.4 Sensor performance indicators

Attribute	Values	Unit
Pressure range	10 ~ 115 (customizable range)	kPa A
Output signal	0.4 ~ 4.65 (Customizable range)	V
Protection level	IP6K9K	
Response time	≤ 3	MS
Upper clamping voltage	96 (customizable)	%FSS
Lower clamping voltage	6 (customizable)	%FSS
Insulation resistance	≥10MΩ/500VDC	MΩ
Operating temperature	-40 ~ 130	°C
Storage temperature	-40 ~ 130	°C

4. Structure and Specification

The sensor's external dimensions (unit: mm, unless tolerances are specified, in accordance with GB/T1804-V) and electrical definition are shown in Figure 5.




Fig.5 GZP6189A

5. Order Guide

GZP 6189 A - A052 E020 B02

Tab.5 Order Guide

GZP	Sencoch
6189 A	Product Categories
A052	Pressure Range A052: 10~115kPa
E020	Power Supply and Output E020: 5V/0.5~4.65V output.
B0 2	Packaging Method B02: Tray

6. Installation Instructions

- 1) Do not immerse the sensor in liquid lubricants.
- 2) Do not touch rubber seals with bare hands; avoid contaminating rubber seals during assembly.
- 3) Do not use hammers, rods, or similar tools to strike the sensor during installation.
- 4) The sensor is for one-time installation only; sensors that have been installed must not be reused.
- 5) Allowable angular deviation in the vertical direction:
 - Under normal conditions: $a = b \leq 90^\circ$
 - When the sensor is exposed to liquid fuel (any type): $a = b \leq 40^\circ$

7. Precautions for use

- 1) The sensor should only be unpacked before it is installed on the engine.
- 2) This sensor is designed for measuring fuel tank pressure in internal combustion engines that use gasoline or diesel fuel. It is not permitted for use in other applications. Please confirm with our company in advance if you require its use in other applications.
- 3) The pressure gauge port is used to measure atmospheric pressure. It is necessary to prevent the pressure gauge port from being blocked during installation (painting) and use.
- 4) Pressure sensors in standard packaging can be transported using ordinary conveyor systems. Please note: Protect the product from moisture, impact, sun damage, and pressure during transportation.
- 5) Please feel free to contact SencoCh for any question.

■ Please confirm under actual usage conditions

Since this specification is for a single product, please verify the performance and quality under actual use to improve reliability.